GL Series Grease and Oil Injectors



High-performance injectors for automatic machine lubrication

- Accurate, adjustable, and reliable lubrication for maintaining your machinery
- Easy to design, set up, and operate
- Flexible to use – easily add or subtract injectors for any system
- Accepts a wide range of lubricants from 10 weight oil to #2 grease
- Large selection of outlet types and manifold quantities for any application

Precision-honed components for reliable operation in challenging environments

Built to Graco Quality Standards

Higher Quality, Higher Performance

Choose durable, long-lasting Graco injectors to perform your lubrication automatically and minimize downtime and maintenance costs.

Seven Outlet Fitting Sizes

Use your preferred size of tubing or hose

Adjustable Injector Output

Adjust output volume on each injector for a custom fit in any application

Visual Indicator Pin

Convenient front-mounted cycle pin indicator confirms that the injector is functioning properly

Wide Range of Manifold Options

Manifolds designed to hold up to 15 injectors decrease installation time

Long-Life Seals

Graco-quality manifold and indicator seals deliver increased productivity

One-Piece, Machined Body

Provides durability not seen in other brands



Long Life Seal Technology

Longer-life seals mean less-frequent replacement or repair and keeps your machines running longer



Manifold Seal Integrity

Exclusive seal design virtually eliminates leaks at the manifold

Technical Specifications

	GL-32	GL-43	GL-33	GL-42
Maximum operating pressure	3500 psi (241 bar)	1000 psi (69 bar)	3500 psi (241 bar)	1000 psi (69 bar)
Minimum operating pressure	1200 psi (83 bar)	750 psi (52 bar)	1200 psi (83 bar)	750 psi (52 bar)
Typical operating pressure	1500 psi (103 bar)	850 psi (59 bar)	1500 psi (103 bar)	850 psi (59 bar)
Reset pressure	200 psi (13.7 bar)	150 psi (10 bar)	200 psi (13.7 bar)	150 psi (10 bar)
Output volume per cycle	0.001 - 0.008 in^3 (0.02 - 0.13 cm^3)		0.001 - 0.003 in^3 (0.02 - 0.05 cm^3)	
Maximum temperature rating	350° F (176° C)			
Recommended fluids	Grease up to NLGI #2	SAE 10 weight oil minimum	Grease up to NLGI #2	SAE 10 weight oil minimum
Instruction manual	313798		334495	

For ordering information on the wide range of GL Series Injectors, visit Graco.com.

Contact us today!

Call **800-533-9655** to speak with a Graco representative, or visit **www.graco.com** for more information.

GRACO

©2014 Graco Inc. 340575 Rev. C 12/14 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.